



Spotwelding Consultants, Inc.

4209 Industrial

Rowlett, TX 75088

Phone: 972-475-0874 Fax: 972-475-5024

Website: www.spotweldingconsultants.com

Product # R4000-XXX/X, R4000 Cooling System

Specifications:

- Factory set at 50 psi adjustable to 100 psi
- 25 gallon reservoir
- 115 / 230 VAC 50 / 60 Hz 1 ph
- 20.4 / 10.2 amp : 60 Hz 1 ph
- 230 / 190 VAC 50 / 60 Hz 3 ph
- 460 / 380 VAC 50 / 60 Hz 3 ph
- 5.4 / 2.7 amp: 60 Hz 3 ph
- 55,000 BTU
- Dimensions: 36"L x 19.5"W x 35"H
- 1/2" FPT SS Pipe - water in and out
- Visible water level / water flow sight glass
- Net weight: 170 lbs / 77 kg

R4000: Rotary GEAR Pump (only)

- 10.0 gpm at 50 psi
- Built in by-pass to tank
- Rebuildable Pump (Repair Kit No. P4018)



ADDITIONAL INFORMATION

System Features	<ul style="list-style-type: none"> • Stainless steel construction eliminates coolant contamination due to electrolysis or chemical reactions. <ul style="list-style-type: none"> • All units are plumbed with copper tubing and reinforced hose. • New extended life pump. • Air flows into patented high efficiency radiator first for maximum efficiency. <ul style="list-style-type: none"> • No external plumbing is required because of closed loop water system. • A water level float gauge and filler cap are combined in a single unit multi-purpose sight glass which enables operator to observe return water at a distance.
-----------------	---